

manual bending equipment for formable profiles

curveline™

Formable trim profiles to bend into shape in order to follow floor contours and other particular geometrical cuts thanks to a softer alloy and special flange sections.

They can be easily and quickly bent saving considerable time on site. Perfect for mosaic works or wood/ceramic combination flooring as well as for framing and edging resin floors laid on site, as they perfectly adapt to more elaborate decorative laying, allowing to create original inlays. The profiles can be formed with a simple hand pressure or employing the special bending equipment.

Laying instructions:

- Cut the profile to the desired length
- Manually curve the profile to the desired shape.
Where necessary use a template or the bending equipment.
- Anchor the profile to the support and if required fasten it with the screws that fit into the holes of the flange section.

The articles available with formable flange are listed here on the right, with the relevant minimum allowed radius, which can be achieved with the bending equipment.

Page	Available Series	Minimum Internal Radius	Minimum External Radius
17	TR - ON / AS / AN / IL	30 cm	30 cm
18	SR - ON / IL	50 cm	50 cm
19	CU 80 ON / CU 100 ON	200 cm	300 cm
23	ZR 80 A* / ZR 100 A*	60 cm	-
23	ZR 80 ON / ZR 100 ON	200 cm	-
28	SP 14 OL / AS	80 cm	80 cm
28	SP 14 OC	100 cm	100 cm

