




entrytec™ BU


Matwell frame to create, finish and protect a recess in the sub-floor that is used to accommodate an entrance barrier mat.

ENTRYTEC BU can accommodate entrance mats up to 23 mm in thickness and is reversible to allow quick installation of the most popular mat thicknesses (18 mm and 23 mm).

The matwell can also be infilled with screed to suit thinner gauge entrance mats. The matwell frame is supplied with fixing connectors for easy on-site assembly and is fixed to the substrate prior to screeding and mat installation.



Illustrated scale dimension 1:1



ENTRYTEC BU 18/23 AS Anodised Aluminium Silver

Reversible profile in aluminium. It can match two different entrance mat thicknesses.

ENTRYTEC BU 18/23 ON Natural brass

Reversible brass profile. It can match two different entrance mat thicknesses.

ENTRYTEC BU* Mounting Accessories

Natural brass fixing clamp to put down in the cement and internal corners bracket in natural aluminium to help junction of 45° cut profiles.

	H+H'		Art.	
Material: Extruded Anodised aluminium	18/23	BU	18/23	AS
Finish: Silver (AS)				
Length: 2,70 metres				

Material: Extruded Natural Brass	18/23	BU	18/23	ON
Finish: Natural (ON)				
Length: 2,70 metres				

		BUS	20	ON
		BUI	20	AN