




coflex™ CR


The modular combination system called "Clip System" allows one to match all possible tile thicknesses still with the same base module, thus resulting in both a time saver and actual material saved. The KJ – Kerajolly profile functions as the perforated side flanges for the laying so to adapt to the different heights of the tiles for wall and floor coverings (e.g. floor height 12,5 mm - wall covering height 8 mm). KERAJOLLY small off-cuts can also be utilized for this purpose.

E.g. of COFLEX assembly for installation: if the thickness of a tile is of 10 mm, utilize the KERAJOLLY KJ 8 mm height profile (page 101) as the combination with the CR base module raises the height by 2 mm matching it then to the 10 mm tile thickness. .



COFLEX CR is expressly conceived to perimeter joint wall/floor coverings supplying sufficient elasticity for the expansion and meeting the cove base hygienic corner cleanliness requirements. It also serves as a sound breaker of the covered surfaces so that trampling of foot steps is not transmitted to the adjacent walls.

COFLEX CR consists of a main curved co-extruded hard/soft combination module Art. CR 16 with Art. series KJ inserts which slide into CR 16 tracks allowing it to adapt to any covering height and providing a perfect anchoring to the tiled covering.



COFLEX CR 16 P* Co-Extruded Synthetic Resin

Main frame co-extruded profile with soft internal cove supplied in different colours. The profile flange inserts are supplied separately as the specific required height needs to be provided.



COFLEX CR Raccordi di derivazione

End caps, internal jointing corner pieces, external and tri-axis jointing pieces. These special pieces help the layer finish off the perimeter laying for two way and three way connections in a most precise and appropriate manner.



| | H=mm | Colour | Art. | | |
|----------------------------------------------------------------|---------|-------------------|------|----|-------------|
| Material: Resinflex + Resinil | modular | Pure white P11 | CR | 16 | P11/P23/P32 |
| Radius: 16mm | | | | | |
| Colour: Pure white (P11), Cement grey (P23), Beige (P32) | | | | | |
| Length: 2,70 metres | | | | | |

| | Description | Art. | |
|--|--------------------|------|----------|
| | Inner corner | CRI | + Colour |
| | Outer corner | CRE | + Colour |
| | Three way junction | CRT | + Colour |
| | Endplug | CRF | + Colour |