



stairtec™ SR

**STAIRTEC SR** is a linear profile, which works very well as stair nosing for steps and finishing trim for all exposed corners, thanks to its quick and practical application covering perfectly well the tile gap over the step while protecting the edge. The SR trim has an extended vertical edge which serves to better cover and protect the joining surfaces or paint finishing, avoiding future fissuring.

Its particular section design makes it suitable to match two different floor thicknesses for example 10 and 12,5 mm with the same reversible profile. Vertical anchorage with dovetail internal cavity groove. Patented system.




Aluminium section



Aluminium and Brass section

(SR 8/15\*)



**TRIMTEC SR-O\* Brass**

The particular straight edge cut profile guarantees protection of vulnerable edges of ceramic stairs. Brass suffers from continuous exposure to humidity leading to oxidation of the surface – a normal polish buffing will bring the product back to its original shine.

**TRIMTEC SR-AS Extruded anodized aluminium- silver**

This profile has a silver coating and is suitable for both indoor or outdoor application with high tolerance to weather agents but less to mechanical impact. During installation excess adhesive and grout should be removed immediately to avoid stains. The exposed surface may change colour or darken in time. Where higher stresses are involved the use of brass profiles is recommended.

**TRIMTEC SR-IS\* Stainless Steel AISI 304 - DIN 1.4301**

This stainless steel profile is AISI 304 standard which ensures high tolerance to corrosion found in laboratories or strong detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, hospitals, public toilets etc. Available in polished (IL) or brushed (IS) version.

**CURVELINE**

TRIMTEC SR series are also available with a special cut flange so they become formable for curved edges and inlays. To order: add the letter D to the product code – for further details see page 47.



	H/H'=mm		Art.	
Material: Brass	8/15 10/12,5	SR SR	8/15 10/12,5	ON/OL ON/OL
Finish: Natural (ON), Polished (OL)				
Length: 2,70 metres				
Improved anchoring on the vertical side				

Material: Extruded anodised aluminium	8/15 10/12,5	SR SR	8/15 10/12,5	AS AS
Finish: Silver (AS)				
Length: 2,70 metres				
Improved anchoring on the vertical side				

Material: Stainless Steel AISI 304	8/15 10/12,5	SR SR	8/15 10/12,5	IL/IS IL/IS
Finish: Polished (IL), Brushed (IS)				
Length: 2,70 metres				

